

Solar powered alarm unit for oil-water separators BAMOBX SOLAR (BBS)



- Monitoring of oil-water separators
- Autonomous complete system
- Field installation
- Alarm signal: or flashing light or GSM
- Battery protection against discharge and overload

APPLICATIONS

Autonomous alarm unit for monitoring oil-water separators according to EN 858.

DESCRIPTION

A BBS system includes alarm unit NivOil CU/12 and a Solar panel to charge a battery, protected against excessive discharge or overload.

NivOil is powered hourly, for 3 minutes, to check for a fault and alarm condition. In case of occurring an alarm, signal is emitted or through a flashing light or through a GSM module.

The working time without sunlight is about 12 days at any period of the year for a reliable monitoring even without sun shining days (referring to Greenwich latitude).

• Option: Flashing light

With the option flashing light, an alarm corresponds to an intermittent light emission (of a Xenon bulb) on the outside of the cabinet. This option is recommended to avoid connecting the NivOIL contact outputs far-away minimizing the cost of installation.

• Option: GSM

With the option GSM, the alarm is transmitted on long distance through a SMS message: idoneous when the system is installed in a remote location. The message SMS sent, indicates the BBS identification, the alarming channel (probe) and a pre-recorded message.

Installation:

The cabinet may be mounted on a wall or on a poll (Yoke U-Bolt Kit provided). The solar panel, with its own fixing system, is adjustable regardless of the position of the cabinet.

The BBS must always be mounted outside the hazardous area. Only NivOil probes can be installed in the hazardous area.

CODE NUMBERS AND REFERENCES

Code	Reference	Description
531 600	BBS-STD	Standard BBS
531 620	BBS-GYR	BBS with flashing light device
531 640	BBS-GSM	BBS with GSM module
Associated probes:		
531 102	NIVOIL-OP/10	Hydrocarbon thickness sensor, 10 m long cable
531 205	NIVOIL-HPS/10	Overfill sensor, 10 m long cable
531 301	NIVOIL-SP/10	Sludge layer sensor 10 m long cable

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Solar powered alarm unit for
oil-water separators
BAMOBX SOLAR (BBS)

03-08-2018

D-531.03-EN-AA

NIV

531-03/1

Details of supply for each version

BBS-STD includes :

- A wall mount cabinet, 300 x 380 x 130 mm
- A yoke U-Bolt Kit for pole mounting
- An alarm unit NivOil
- A battery, 7 Ah
- A controller module to protect the battery against excessive discharge or overload.
- A solar panel, 5 Wc, on adjustable holder

BBS-GYR includes:

- A complete system BBS-STD
- A flashing light device on the front of the cabinet

BBS-GSM includes:

- A complete system BBS-STD
- A GSM module, inside the cabinet

TECHNICAL FEATURES

CABINET

Operating temperature	-25 ... +60 °C
Dimensions	300 x 380 x 130 mm
Protection	IP 56
Mass	5.8 kg

SOLAR PANEL

Power	5 Wc
Technology	Polycrystalline multi panel
Dimensions	365 x 195 mm
Mass	1.8 kg

BATTERY

Power	7 Ah
Dimensions	150 x 100 x 65 mm

FLASHING LIGHT DEVICE

Dimensions	Ø 75 x 45 mm
------------	--------------

GSM MODULE

Dimensions	75 x 45 x 25 mm
	Refer to data-sheet 248-02

EC Conformity: The instrument meets the legal requirements of the current European Directives

NivOil sensors: All features on data-sheet 531-02

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Solar powered alarm unit for
oil-water separators

BAMOBX SOLAR (BBS)

03-08-2018

D-531.03-EN-AA

NIV

531-03/2