



Cable and pulleys , gastight level indicator SFA/E



Plastic version with graduated ruler option



Float and cable in stainless steel (variant)

- For storage tanks
- Gastight indicator
- Protection from emitted vapors
- Works without power supply
- Options: Level switches; Graduated ruler

APPLICATIONS

- Liquid storage (neutral, acidic or basic)

DESCRIPTION

The SFA/E displays the level in a sealed storage tank. The equipment is designed for liquids that emit harmful or corrosive vapors, or to protect the stored liquid from external atmosphere.

The float, suspended to a rope (or cable) supported by 2 pulleys, drives a counterweight inside the guide tube, showing the level of the liquid. The pulleys are enclosed in PVC elbows with an anti-derailment system, ensuring perfect rope guidance. Elbows are connected together with a PVC transfer tube. The counterweight is guided in a tube Ø 63 mm, tightly closed. The unit is connected to the tank by a DN 100 PN10/16 PVC loose flange (other on request).

The guide tube is fixed through collars, and can support a PVC graduated ruler and/or level switches actuated by the magnetic counter weight (see data-sheet 583-03).

CODE NUMBERS AND REFERENCES

Code 583702

Reference SFA/E/M

Complete gastight set comprising the following elements:

- 5 m long rope, PP, Ø 3 mm
- 1 Float, PPH, Ø 98 mm (S.G. min. 0.94)
- 1 Magnetic counterweight, PVC, Ø 50 mm, for tube Ø 63 x 57 mm
- 2 Gastight pulleys
- 4 PVC transfer pipes Ø 40 lg 500mm each + 2 connecting sleeves
- 1 PVC loose flange and collar for tank fitting DN100 PN10
- 1 Bottom tap for guide tube
- Union couplings

Guide tube not included: to order separately at proper length

Variant with float and stainless steel cable : Code 583703

Code 583720

Reference Kit SFA/E

Partial gastight set comprising the following elements:

- 5 m long rope, PP, Ø 3mm
- 1 Float, PPH, Ø 98 mm (S.G. min. 0.94)
- 1 Magnetic counterweight, PVC, Ø 50 mm, for tube Ø 63 x 57 mm
- 2 Gastight pulleys

Code 583570

Reference TT/SFA

Guide tube, transparent PVC, Ø 63 mm

Length to confirm on inquiry and purchase order

To facilitate handling during assembly and/or to meet transport requirements, the guide tube and optional graduated ruler can be made in several parts.

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Cable and pulleys , gastight
level indicator
SFA/E

28-06-2024

D-583.02-EN-AF

NIV

583-02 /1