

Pressure gauge guard for tri-clamp mounting D301



- Quickly dismountable from piping
- Laser welded diaphragm
- Operating ranges: -1 ... 0 ... 40 bar
- For tri-clamp fitting

APPLICATIONS

This pressure gauge guard is designed for food, beverage, cosmetic and pharmaceutical industries.

TECHNICAL FEATURES

Operating range	-1 ... 0 ... 40 bar
Filling	Food grade oil, -20 ... +140 °C
Body	AISI 316
Diaphragm	AISI 316 L

Instrument connection	or BSP-F 1/2" or NPT-F 1/2" or BSP-F 1/4" or NPT-F 1/4" or BSP-F 3/8"
-----------------------	---



Process connection	For tri-clamp 1" or 1 1/2" or 2" or 2 1/2"
--------------------	--

EC Conformity: The instrument meets the legal requirements of the current European Directives.

DIMENSIONS:

Process connection

Tri-clamp size 1"	Diaphragm (OD/ED) 35/25 mm Ranges from 0...4 bar up to 0...40 bar
Tri-clamp size 1 1/2"	Diaphragm (OD/ED) 38/32 mm Ranges from 0...2 bar up to 0...40 bar
Tri-clamp size 2"	Diaphragm (OD/ED) 48/40 mm Ranges from 0...1 bar up to 0...40 bar
Tri-clamp size 2 1/2"	Diaphragm (OD/ED) 62/52 mm Ranges from -1...0 bar up to 0...40 bar



CODE NUMBERS AND REFERENCES

Code	Description
D301	All stainless steel pressure gauge guard for tri-clamp fitting
812 xxx	Instrument fitting & tri-clamp size: O/A; WITHOUT ferrule, gasket, clamp Filling: Food grade oil, -20 to +140 °C

Options on request: Certificates, other types

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Pressure gauge guard for
tri-clamp mounting
D301

09-02-2022

D-812.30-EN-AB

PR

812-30/1