

CODE NUMBERS AND REFERENCES

Code	Reference	ND	FLARE couplings	Range	
				l/min	l/h
776 008	BAMOFLONIC PFA DN7	7	3/8"	0.09 ... 6.00	5.4 ... 360
776 011	BAMOFLONIC PFA DN10	10	1/2"	0.3 ... 24	18...1440
776 016	BAMOFLONIC PFA DN15	15	3/4"	0.9 ... 60	54...3600
776 021	BAMOFLONIC PFA DN20	20	1"	1.2 ... 120	72...7200

On request: Low flow-rate, from 0.03 ... 6.0 l/min (ND 7 / raccord 3/8")

DIMENSIONS

ND	Fittings	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	Mass [kg]
7	3/8"	218	120	79	16	77	63	48	1.3
10	1/2"	219.5	120	79	16	78.5	64	48	1.3
15	3/4"	227	120	82	19	82	64	48	1.3
20	1"	251	120	91.5	25	94	64	48	1.6

REMOTE DISPLAY UNIT

Code 776002
Reference Remote display for BAMOFLONIC - PFA

Housing IP 65; in PSU (Polysulfone),
anodized aluminum wall bracket
Power supply 18 ... 30 V DC, 3.6 W
Connector M12; 5 pins
Ambient temperature +5 ... +60 °C
Storage temperature 0... +70 °C
Display LCD; Backlighted
Keypad 4 keys

EC Conformity: The instrument meets the legal requirements of the current European Directives

Remote display unit is supplied with a 5 m long cable (connector 5 pins fitted), a Te connector and an electric plug "Europlug" (5 pins connector). The set allows display and modification of settings of flow-meter, as well as recovering of output signals.

